



CLIVET SPA
Via Camp Lonc 25, Z.I. Villapaiera - 32032 Feltre (BL) - Italy
Tel. + 39 0439 3131 - Fax + 39 0439 313300 - info@clivet.it

MideaGroup
humanizing technology

www.clivet.com
www.clivetlive.com



PRODUCT CATALOGUE

2022

Split Floor Standing



Powerful Airflow

Equipped with a powerful DC motor and a large-diameter centrifugal blower wheel to achieve an airflow up to 2300m³/h.



15 Meters Long Distance Wind Blast

The large air outlet and six large air directing blades enable an airflow distance of up to 15m.



Hidden VLED Display

The hidden VLED display screen is easy to read yet beautiful.



Wind Avoid Me

With one tap of button, the airflow direction is automatically adjusted to the maximum angle to prevent direct cold/hot drafts.



3D Airflow

Midea's 3D airflow function combines vertical and horizontal auto-swing to spread comfort more widely throughout the room.



Floor Standing



Floor Standing



Model Name	Indoor	CFTGA-36CRN1-QC1W	CFT4GA-48CRN1-RC1W	CFT4GA-55CRN1-RC5W
	Outdoor	COTDUL-36CN1-QC1W	COT4DUL-48CN1-RC1W	COT4EUL-55CN1-RC5W
ESMA Rating		2	1	2
Capacity (Btu/h)	Cooling	T1: 33000 T3: 29200	T1:48000 T3:43000	T1: 54000 T3: 48000
	Heating	-	-	-
Power input (W)	Cooling	T1: 2980 T3: 3500	T1:4400 T3:5350	T1: 4520 T3: 5550
	Heating	-	-	-
EER (Btu/h)/W	Cooling	T1: 11.07 T3: 8.34	T1:10.91 T3:8.04	T1: 11.95 T3: 8.65
	Heating	-	-	-
Rated Current (A)	Cooling	T1: 13.22 T3: 15.42	T1:8.50 T3:9.50	T1: 8.00 T3: 9.32
	Heating	-	-	-
Power supply (Ph/V/Hz)	/	1/220-240/50	3/380-415/50	3/380-415/50
Indoor air flow (m³/h) (Turbo/Hi/Lo)	/	2040/1910/1650	2396/2280/1840	2280/2050/1950
Refrigerant	/	R410A	R410A	R410A
Indoor				
Net dimension (mm)	W*D*H	610x390x1925	610x390x1925	610x390x1925
Packing dimension (mm)	W*D*H	765x515x2070	765x515x2070	765x515x2070
Net/Gross weight (kg)	/	55.5/73.7	57.2/75.7	56.7/76.1
Indoor noise level [dB(A)](Turbo/Hi/Lo)	/	53/51/44	58/57/51	57/54/53
Indoor Controller Model	/	RG57	RG57	RG57
Outdoor				
Net dimension (mm)	W*D*H	946x410x810	900x350x1170	952x415x1333
Packing dimension (mm)	W*D*H	1090x500x875	1032x443x1307	1095x495x1480
Net/Gross weight (kg)	/	72.4/76.9	89.6/100	112.6/126.6
Outdoor noise level [dB(A)]	/	62	62	61
Operation ambient temperature	°C	18~52°C	18~52°C	18~52°C
Refrigerant piping				
Liquid side/ Gas side	mm(inch)	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ22(3/8"/7/8")
Max. pipe length	m	30	50	50
Max. difference in level	m	20	30	30

NOTES:

The condition is on below:

1. T1 condition:

Outdoor: 35°CDB/24°CWB - Indoor: 27°CDB/19°CWB.

2. T3 condition:

Outdoor: 46°CDB/24°CWB - Indoor: 29°CDB/19°CWB.

3. Sound measured at 1.0m away from the center of the unit.

4. ESMA rating is based on UAE.S 5010-1:2019.